

DIMENSIONS IN mm [inches]



# AiM MXT 1.3 Strada

10 inches TFT Dash

## Technical specifications


<b>Display</b>	10" TFT
<b>Resolution</b>	1280x480 pixels
<b>Contrast</b>	1,100:1
<b>Brightness</b>	800cd/m2
<b>Ambient light sensor</b>	Yes
<b>Alarm LEDs</b>	6 configurable RGB LEDs
<b>Shift Lights</b>	10 configurable RGB LEDs
<b>CAN connections</b>	2
<b>ECU connection</b>	CAN, RS232 or K-Line to 1,000+ industry leading ECUs
<b>External modules</b>	GPS Module, Channel Expansion, TC Hub (necessary to connect K thermocouples), Lambda Controller, SmartyCam 3
<b>Analog/digital inputs</b>	8 fully configurable, max 500 Hz each
<b>Digital inputs</b>	1 Speed input, coil RPM input
<b>Digital outputs</b>	1 (1 Amp max)
<b>Second CAN</b>	Yes
<b>Body</b>	Anodized Aluminum
<b>Pushbuttons</b>	Metallic
<b>Connectors</b>	2 AMPSEAL connectors + 1 Binder connector
<b>Dimensions</b>	278x135x43.2 mm
<b>Weight</b>	1,100 g
<b>Power consumption</b>	450 mA
<b>Waterproof</b>	IP67



# AiM MXT 1.3 Strada

10 inches TFT Dash

## Pinout



Pin	Function
1	Analog input 1
2	Analog GND
3	+Vb output
4	+Vreference
5	Analog input 2
6	Analog input 3
7	Analog GND
8	+Vb output
9	+Vreference
10	Analog input 4
11	Analog input 5
12	Analog GND
13	+Vreference
14	Analog input 6
15	Analog input 7
16	+Vreference
17	Analog input 8
18	Speed input
19	GND
20	Low Side output
21	RPM input
22	CAN 2+
23	CAN 2-

Pin	Function
1	Video input 1
2	GND
3	+Vb output camera
4	GND
5	Video input 2

Pin	Function
1	9-15v Power input
2	Battery GND
3	CAN+ Exp
4	GND
5	+Vb out CAN
6	CAN- Exp
7	+Vb Ext CAN
8	CAN1+/ECU RS232TX
9	CAN1-/ECU RS232RX
10	K Line ECU
11	USB D+
12	USB D-
13	USB GND
14	Reserved